

Ultra High Vacuum Pumps

TiTan
Ion Pumps

DIGITEL
Ion Pump Controllers

TSP
Titanium Sublimation Pumps

NEG
Non-Evaporable Getter Pumps

Contents

Ultra High Vacuum Pumps

Products

TiTan Ion Pumps

Overview	5
Ion Pump Applications	6
Small Ion Pumps (MINI – 75S)	7
Low Profile Ion Pumps (100L – 1200LX)	7
Tall Profile Ion Pumps (150TV – 600TV)	7
TiTan Ion Pump Elements	7

DIGITEL Ion Pump Controllers

Overview	10
DIGITEL SPCe – Small Pump Controller	11
DIGITEL QPC – Quad Pump Controller	11
DIGITEL MPCq – Multiple Pump Controller	11
Ion Pump Compatibility	12

TSP Titanium Sublimation Pumps

Overview	14
TSP Filament Cartridge	15
Liquid Cryoshroud	15
Ambient Sputter Shield	15
DIGITEL TSPq Controller	15

NEG Non-Evaporable Getter Pumps

NEG 50NP – NEG 400NP	18
DIGITEL SPC _{NEG} – NEG Pump Controller	19



Company

Gamma Vacuum specializes in the design, manufacture and distribution of ion and titanium sublimation pumps as well as NEG pumps and their combinations, serving customers across a diverse range of scientific applications, including R&D and High Energy Physics. Their employees are committed to being the primary source of knowledge in Ultra High Vacuum and expertise globally, delivering consistent superior quality, at a low initial and operational cost.

Based in Shakopee, Minnesota, USA, Gamma Vacuum was established in 2003. Leybold have been distributing and supporting Gamma products for many years.

Log in on the Gamma website:

www.gammavacuum.com

for specification sheets, manuals and more information.

Any questions? We can customize your ion pump setup. Please contact your local Leybold sales and ask for customer work request (CWR).

The CWR is a questionnaire which is used to specify the customized ion pump system.



TiTan Ion Pumps



Ion pumps are used in a wide variety of high and ultra-high vacuum (UHV) environments. They can reach the lowest possible vacuum for an economical cost. In addition, ion pumps have some technical advantages over other technologies:

Advantage for the User

- Vibration free operation
- Low operational cost
- Bakeable
- Low maintenance
- Pressure indication
- Permanent gas capture
- Radiation tolerance
- Long operational life
- Non-contaminating technology

Characteristics

Lifetime

All Gamma Vacuum ion pumps are designed to operate for 45,000 – 50,000 hours at 1×10^{-6} mbar. Lifetime increases linearly with decreased pressure. At 1×10^{-9} , for example, an ion pump can last for many years.

Ultimate Pressure

Ion pumps are capable of reaching pressures below 1×10^{-10} mbar. Ultimate pressure of an ion pump is dictated by overall system conditions and materials.

Vacuum Processing

Ion pumps are shipped under vacuum at pressures less than 1×10^{-10} mbar. Certificates of conformance are provided and record all leak check points and pump characteristic values. RGA scans can be provided upon request.

Port Configurations

Each ion pump can be configured with a variety of pumping port options. Additional ports are available in most designs on the top, bottom, or side and can accommodate TSP or non-evaporable getter (NEG) modules.

Feedthroughs

Gamma Vacuum has standardized on the commercially available 10kV SHV feedthrough since 1996. For legacy purposes, alternate feedthroughs are available.

Heaters

Integrated heaters can be added to ion pumps for economical and efficient baking.

Cables

In addition to incorporating the SAFE-CONN interlock system, high voltage cables are made of flexible silicone materials that are bakeable and have high radiation tolerance.

Ion Pump Applications

Ion Pump Size Pumping Speed (l/s)				
	2-3	3-20	20-75	100+
Application				
Industry and Medical Processes				
Radar	■			
Traveling Wave Tubes (TWT)	■			
Klystrons	■			
X-Ray Tube Evacuation	■	■		
X-Ray Sources	■	■		
Treatment & Diagnostics		■	■	
Semiconductor				
Critical Dimension SEM (CD SEM)		■	■	
Lithography			■	■
Instrumentation				
Electron Microscopes (SEM/TEM)		■	■	
Focused Ion Beam (FIB)		■	■	
Scanning Probe Microscope (SPM)		■	■	■
Surface Analysis (AES, XPS, SIMS, EDX)			■	■
Mass Spectrometry (MS)			■	■
Molecular Beam Epitaxy (MBE)			■	■
High Energy Physics				
Accelerators			■	■
Boosters			■	■
Storage Rings			■	■
Front Ends			■	■
Beam Lines			■	■
End Stations			■	■
Free Electron Lasers (FEL)			■	■
Laser Interferometers			■	■

Small Ion Pumps (MINI – 75S)



Small ion pumps come in a wide variety of sizes and configurations. Gamma Vacuum maintains stock of the most common configurations for same-day shipping. These pumps have the added advantage that they can be mounted in any orientation without additional support.

Low Profile Ion Pumps (100L – 1200LX)




Low Profile ion pumps are under 12 in. (300 mm) high for standard configurations. The closed magnetic loop of these pumps reduces the stray magnetic field created by the pump making these pumps ideal for any type of charged particle application.

Tall Profile Ion Pumps (150TV – 600TV)



Tall Profile ion pumps are designed for mounting in narrow locations and matching competitive dimensions. These pumps are built to order and designed to fit into locations where a Low Profile ion pump might not fit.

TiTan Ion Pump Elements



TiTan ion pump elements are “tuned” for specific pumping applications. Surfaces are chemically processed to remove potential surface contaminants and provide maximum adhesion for extended lifetime. Ceramics are optimally shielded to reduce exposure to sputtered material.

- TiTan CV (Conventional)
 - two titanium cathodes for high pumping speed of reactive gases.
- TiTan DI (Differential)
 - a titanium and tantalum cathode for maintained pumping speeds of reactive gases and long term stability of noble gases.
- TiTan TR
 - classic triode element for higher pressure operation

Technical Data

Titan Ion Pumps

	Pumping Speed l/s	Weight kg (lbs)	Available Elements	Available Ports	Available Feedthroughs	Option: Integrated TSP/NEG
MINI	0.2	0.35 (0.8)	DI	1V	MN	N
3S	3	0.45 (1.0)	CV / DI	CU / 1V / 1H / 1D	5K / OV	N
5S	5	2.3 (5)	CV / DI	2V	5K / SC	N
10S	10	6 (13)	CV / DI	2H	SC / OV / FI	N
25S	25	9 (20)	CV / DI / TR / CX / DX	2V / 2H / 2D / 4V / 4D	SC / OP / OV / VR / FI	TSP / N0 / N1
45S	45	16 (34)	CV / DI / TR / CX / DX	2V / 2H / 2D / 4V / 4D	SC / OP / OV / VR / FI	TSP / N0 / N1 / N2
75S	75	22 (48)	CV / DI / TR / CX / DX	2V / 2D / 4V / 4D / 6S / 62	SC / OP / OV / VR / FI	TSP / N0 / N1 / N2 / N3
100L	100	29 (62)	CV / DI / TR	6S / 6D / 8S / 8D	SC / OP / OV / VR / FI	TA / NG
150T	150	32 (70)	CV / DI / TR	6S / 6D / 6P / 8S / 8D / 8P	SC / OP / OV / VR / FI	TC / TA / NG
150TV	150	32 (70)	CV / DI / TR	6S / 6D / 6P	SC / OP / OV / VR / FI	TC / TA / NG
200L	200	50 (112)	CV / DI / TR	6S / 6D / 8S / 8D	SC / OP / OV / VR / FI	TC / TA / NG
200T	200	50 (112)	CV / DI / TR	6S / 6D / 6P / 8S / 8D / 8P	SC / OP / OV / VR / FI	TC / TA / NG
300L	300	66 (145)	CV / DI / TR	8S / 8D	SC / OP / OV / VR / FI	TC / TA / NG
300T	300	66 (145)	CV / DI / TR	8S / 8D / 8P	SC / OP / OV / VR / FI	TC / TA / NG
300TV	300	66 (145)	CV / DI / TR	8S / 8D / 8P	SC / OP / OV / VR / FI	TC / TA / NG
400L	400	67 (148)	CV / DI / TR	8S / 8D	SC / OP / OV / VR / FI	TC / TA / NG
400LX	400	95 (210)	CV / DI / TR	8S / 8D / 8P	SC / OP / OV / VR / FI	TC / TA / NG
500T	500	96 (212)	CV / DI / TR	8S / 8D / 8P	SC / OP / OV / VR / FI	TC / TA / NG
600L	600	103 (226)	CV / DI / TR	8S / 8D / 10 / 18	SC / OP / OV / VR / FI	TC / TA / NG
600LX	600	122 (270)	CV / DI / TR	8S / 8D / 8P / 10 / 18 / 19	SC / OP / OV / VR / FI	TC / TA / NG
600TV	600	109 (243)	CV / DI / TR	8S / 8D / 8P	SC / OP / OV / VR / FI	TC / TA / NG
800LX	800	127 (280)	CV / DI / TR	8S / 8D / 10 / 18	SC / OP / OV / VR / FI	TC / TA / NG
1200LX	1200	206 (452)	CV / DI / TR	8S / 8D / 10 / 18	SC / OP / OV / VR / FI	TC / TA / NG
XW	Xl/s	25 (56)	CV / DI	2D	SC / FI	

For the meaning of abbreviations, like CV, DI, 2H, SC, FI, NG, etc., please check out the ordering information table on the opposing page.

Log in on the Gamma website: www.gammavacuum.com for specification sheets, manuals and more information.

Ordering Information

Part No.:

200L	DI	8D	SC	2	TA
Pump	Element	Flange	Feedthrough	Heater*	Integrated TSP/NEG
MINI	Conventional diode CV	Copper Tube CU	Mini MN	None N	None N
3S	Noble diode DI	Vertical DN16 (1.33") 1V	5kV SHV 5K	120 V 1	TSP single filament TSP
5S	Conventional diode XHV CX	Horizontal DN16 1H	10kV SAFECONN SC	240 V 2	50l/s NEG (25/45/75) N0
10S	Noble diode XHV DX	2 ports DN16 1D	Perkin Elmer OP		100l/s NEG (25/45/75) N1
25S	Triode TR	Vertical DN40 (2.75") 2V	Old Varian OV		200l/s NEG (45/75) N2
45S		Horizontal DN40 2H	Varian StarCell® VR		300l/s NEG (75) N3
75S		2 ports DN40 2D	Fisher Interlock FI		TSP & Cryoshroud (not 100L) TC
100L		Vertical DN63 (4.5") 4V			TSP & Ambient Shield TA
150T		2 ports DN63/40 (4.5"/2.75") 4D			400l/s NEG NG
150TV		Single DN100 (6") 6S			
200L		2 ports DN100/40 (6"/2.75") perpendicular 62			
200T		2 ports DN100/40 (6"/2.75") inline 6D			
300L		2 ports DN160/100 (8"/6") perpendicular 6P			
300T		Single DN160 (8") 8S			
300TV		2 ports DN160 inline 8D			
400L		2 ports DN160 perpendicular 8P			
400LX		Single DN200 (10") 10			
500T		2 ports DN200/160 (10"/8") inline 18			
600L		2 ports DN200/160 (10"/8") perpendicular 19			
600LX					
600TV					
800LX					
1200LX					
XW					

* option only for 10S and bigger, heater option not available (N) for MINI, 3S and 5S

The above example explains what is behind the part number **200LDI8DSC2TA**. It's a 200 l/s ion pump with a low profile and a noble diode element. It has two opposing flanges ('inline') with a diameter of DN 160 (8"). It uses the SAFECONN feedthrough and has an electrical heat-

er with a supply voltage of 240 V. The ion pump contains an integrated TSP with ambient sputtering shield (for more information, please check out the TSP section). For more possibilities or restrictions, please check out the technical data table on the opposing page.



GAMMA
V A C U U M

DIGITEL Ion Pump Controllers



The DIGITEL family of Ion Pump Controllers offers the right balance of performance, power and protection.

Advantage for the User

Ease of Use

Each DIGITEL has a highly visible display. The SPCe has an easy-to-read LCD that displays pressure, current and voltage. The QPC and MPCq are each fully controlled with an intuitive touch panel LCD. Digital resolution down to 1 nA is possible depending on pump size and current requirements.

Communications

Serial communications (RS232, RS422, and RS485) are standard on all DIGITEL products. Ethernet protocol for advanced facility and instrumentation communications is available on all units.

Connectivity

Each DIGITEL has programmable analog and interlock capabilities. This allows for optimal flexibility when integrating with standard or legacy set-point and analog monitoring systems.

Operator Safety

The integrated SAFECONN high voltage interlock system eliminates electrical shocks and false positive pressure readings. The controller automatically shuts off high voltage when the cable is disconnected from the ion pump or controller end. The system is isolated and guarantees ground, high voltage, and safety connectivity that prevents accidental arcing.

DIGITEL Flexibility

The DIGITEL line is flexible enough to control a wide variety of ion pump and TSP configurations. The QPC and MPCq can operate up to four ion pumps simultaneously or independent operation of one or two ion pumps, respectively. The MPCq is capable of controlling one or two TSP cartridges independently.

DIGITEL SPCe – Small Pump Controller



The SPCe is a versatile way to fully operate ion pumps 0.2 – 75 l/s with up to 40 mA (50 watts) of power. An LCD pressure/current/voltage display along with standard serial communications makes the SPCe able to accommodate the needs of basic and advanced users. Nano amp resolution provides gauging capabilities using the appropriate ion pump set-up.

DIGITEL QPC – Quad Pump Controller



Ion pumps 100 l/s and larger required higher currents for starting and higher pressure operation. The QPC supplies up to four ion pumps with 125 mA (125 watts) each. The easy-to-read color touchscreen display simultaneously displays pressure, current, and voltage. Standard serial and standard Ethernet communications along with legacy set-point and analog outputs allow for easy system integration. The QPC fits into any rack at just 3U high and 1/2 rack wide.

DIGITEL MPCq – Multiple Pump Controller



Ion Pump Control

The MPCq allows for high current control of one or optionally two ion pumps independently or up to four in parallel with 500 mA (1000 watts). At 3U high and a full rack in width, the MPCq is ideal for operating a wide variety of ion pump configurations on any system.

TSP Control

A TSP can be fully operated from the LCD touchscreen of the QPC or MPCq. They can be fired manually or automatically based on the pressure of either ion pump the controller is monitoring. Timed modes also let the user have full control over exact parameters of operation. A single remote controller can operate up to eight TSP filaments.

Ion Pump Compatibility

Ion Pump Size					
	SPCe	QPC	MPCq	TSP	
Small Ion Pumps					
MINI	■				
3S	■				
5S	■	■			
10S	■	■			
25S	■	■	■		
45S	■	■	■		
75S	■	■	■		
Low Profile Ion Pumps					
100L		■	■	■	
200L		■	■	■	
300L		■	■	■	
400L			■	■	
400LX			■	■	
600L			■	■	
600LX			■	■	
800LX			■	■	
1200LX			■	■	
Tall Profile Ion Pumps					
150TV		■	■	■	
300TV		■	■	■	
600TV			■	■	

Technical Data

Controller

		SPCe	QPC	MPCq
Input power	Voltage	90 – 240 or 24 VDC	100 – 240	90 – 230 or 200 – 240
	Frequency	48 – 62	50 – 60	48 – 62
Output power	Independent outputs	1	1 – 4	1 or 2
	Open circuit voltage	±3000 – 7000 programmable	±3000 – 7000 programmable	±5600 or 7000
	Current (maximum)	40	125	500
	Watts (maximum)	50	4 x 125	1000
	Resolution	1	1	100
High voltage connections		One 10kV SHV or Fischer	1-4, 10kV SHV or Fischer	1-4, 10kV SHV or Fischer
Display	Type	LCD	Wide VGA Touchscreen Color LCD	1/4 VGA Touchscreen LCD
	Readouts	Pressure, current, voltage, and programmable options	Pressure, current, voltage, and programmable options	Pressure, current, voltage, and programmable options
Setpoints		One relay, one TTL	Four relay, four TTL	Four relay, four TTL
Analog outputs		linear configurable		
Voltage		linear or logarithmic, configurable		
Current / pressure				
Communications		Local/Remote/Full Ethernet (optional) Serial: 232, 422, 485	Local/Remote/Full Ethernet (standard) Serial: 232, 422, 485	Local/Remote/Full Ethernet (optional) Serial: 232, 422, 485
Conformity to norms		EN 55011 Class A, IEC 801-2 EN 801-3, IEC 801-4, EN 61010-1		
Weight	kg	1.5	9.5	16.8 / 25.4 (min./max.)
	lbs	3.3	21	37 / 56 (min./max.)
Size		2U high, 1/4 rack wide 313 mm (12.3 in.) deep	3U high, 1/2 rack wide 438 mm (17.2 in.) deep	3U high, full rack wide 438 mm (17.2 in.) deep
Additional features		SAFECONN AUTOSTART/AUTORUN High Voltage Enable Fowler-Nordheim Calibration High-Pot Capability	SAFECONN AUTOSTART/AUTORUN High Voltage Enable Remote TSP Control	SAFECONN AUTOSTART/AUTORUN High Voltage Enable Remote TSP Control

Log in on the Gamma website: www.gammavacuum.com for specification sheets, manuals and more information.

Ordering Information


Part No.									
QPC	1	P	S	1	U1	SS	NI		
Controller	HV Channels	HV Polarity	Connector Style	Connections/ Channel	Input Voltage	Communications	TSP Control		
QPC ¹⁾	One 1	Positive (CV/DI) P	10kV (SAFECONN) S	One output 1	110 V, US U1	Serial/Ethernet SS	Not Installed NI		
MPCq ²⁾	Two 2	Negative (TR) N	Fisher (Interlock) E	Two outputs 2	220 V US U2	Profibus/Serial/Ethernet PRS	Remote TSP Control ST		
SPC ³⁾	Three 3			Three outputs 3	230 V, EC E2	Ethernet ES	Dual Remote TSP Control DT		
	Four 4			Four outputs 3	230 V, UK K2	Serial (User Configurable) SS	Internal Remote TSP Control IT		
230 V, AU A2									

¹⁾ no Internal Remote TSP Control

²⁾ 1 or 2 HV Channels only, Communications "SS" and "PRS" only

³⁾ 1 HV Channel only, 1 output only, Communications "ES" and "SS (Serial (User Configurable))" only, TSP Control not installed

TSP Titanium Sublimation Pumps



Titanium Sublimation Pumps (TSPs) are often used in combination with ion pumps or independently to remove reactive gases from the vacuum environment. Combined with an ion pump, the TSP allows for low ultimate pressures in a shorter amount of time. All TSP components are bakeable to 400°C.

Advantage for the User

Ease of Use

The TSP and MPCq controllers are each fully controlled with an intuitive touch panel LCD.

Filaments

Each titanium-molybdenum filament contains 1.5 grams of usable titanium and averages 20 hours of operation.

Connectivity

TSP cables have MS style connectors that are bakeable and radiation resistant.


Safety

High currents travel over distances up to 15 meters through bakeable and radiation-resistant insulated and strain relief cabling.

DIGITEL Flexibility

The DIGITEL line is flexible enough to control a wide variety of ion pump and TSP configurations. The QPC and MPCq can operate up to four ion pumps simultaneously or independent operation of one or two ion pumps respectively. The MPCq and QPC are capable of controlling one or two TSP cartridges independently from the remote TSP controller or the MPCq's optional internal TSP (iTSP).

TSP Filament Cartridge



The filament cartridge is mounted on a 2- 3/4" CFF (DN 40 CF). The feed-through supports three titanium-molybdenum filaments and a return path for ground isolation. Each filament contains 1.5 grams of usable titanium and averages 20 hours of operation.

Liquid Cryoshroud



The liquid cryoshroud consists of a double walled, type 304L stainless steel cylinder with two liquid nitrogen feedthroughs with flare type fittings. It provides 1578 cm² (245 in.²) of liquid nitrogen cooled surface area that provides pumping speeds up to 12,000 l/s for hydrogen (see table). The shroud is mounted on an 8 in. CFF (DN 160) or 10 in. CFF (DN 200).

Ambient Sputter Shield



The ambient sputter shield economically maximizes surface area when cooling is not practical or possible. It provides 827cm² (128 in.²) of ambient temperature surface area that provides pumping speeds up to 2,200 l/s for hydrogen (see table). The shield is mounted on an 8 in. CFF (DN 160) or a 6 in. CFF (DN 100).

DIGITEL TSPq Controller



The TSPq controller has an easy-to-read color touchscreen display that displays all manual or programmed firing parameters. Manual operation is as simple as pressing one button. Programming is just as easy by viewing all programming options on one screen. The TSPq controller can operate up to 8 TSP filaments.



Technical Data

Controller

		DIGITEL TSPq	Remote rTSP
Input power			
Voltage	V	100 – 120 or 200 – 240	100 – 120 or 200 – 240
Frequency	Hz	47 – 63	47 – 63
Output power			
Independent outputs		1	1
Current (maximum)	A	55	55
Watts (maximum)	W	800	800
Resolution	A	0.1	0.1
High current connections		1 - 2 MS type ¹⁾ configurable	1 - 2 MS type ¹⁾ configurable
Display			
Type		7" TFT WVGA 800 x 480 color LCD touchscreen	–
Readouts		Current, on-time, and programmable options	Current, on-time, and programmable options via MPCq/QPC
Analog outputs			
Voltage		linear configurable	linear configurable
Current / pressure		linear or logarithmic, configurable	linear or logarithmic, configurable
Control modes		Manual, programmed, or remote	Manual, programmed, or remote
Communications		Ethernet Serial: RS-232, RS-485 2 wire, RS-485 4 wire Profibus (optional, coming soon)	Ethernet via MPCq Serial: RS-232, RS-422 2 wire, RS-485 4 wire via MPCq
Conformity to norms		EN 55011 Class A, IEC 801-2 EN 801-3, IEC 801-4, EN 61010-1	EN 55011 Class A, IEC 801-2 EN 801-3, IEC 801-4, EN 61010-1
Weight	kg lbs	16 36	13.1 29
Size (L x W x H)	mm in.	3U high. 1/2 rack wide 462 x 208 x 130 – 18.2 x 8.2 x 5.1 –	– 293 x 219 x 130 (min.) 293 x 219 x 150 (max.) 12 x 9 x 5 (min.) 12 x 9 x 6 (max.)
Additional features		TSP interlock	TSP interlock via MPCq

¹⁾ Amphenol MIL-DTL-5015 P/N 97-3102A-24-22S(946)

Log in on the Gamma website: www.gammavacuum.com for specification sheets, manuals and more information.

Ordering Information

Controller

		DIGITEL TSPq	Remote rTSP
		Part No.	Part No.
Single MS connector			
110 V, US		TSPQ1U1SSN	RTSP1U1NNN
220 V, US		TSPQ1U2SSN	RTSP1U2NNN
230 V, EC		TSPQ1E2SSN	RTSP1E2NNN
230 V, UK		TSPQ1K2SSN	RTSP1K2NNN
230 V, AU		TSPQ1A2SSN	RTSP1A2NNN
Dual MS connector			
110 V, US		TSPQ2U1SSN	RTSP2U1NNN
220 V, US		TSPQ2U2SSN	RTSP2U2NNN
230 V, EC		TSPQ2E2SSN	RTSP2E2NNN
230 V, UK		TSPQ2K2SSN	RTSP2K2NNN
230 V, AU		TSPQ2A2SSN	RTSP2A2NNN
Remote Connection			
110 V, US		TSPQ0U1SSST	–
220 V, US		TSPQ0U2SSST	–
230 V, EC		TSPQ0E2SSST	–
230 V, UK		TSPQ0K2SSST	–
230 V, AU		TSPQ0A2SSST	–

Technical Data

		TSP Filament Cartridges		Liquid Cryoshroud		Ambient Sputter Shield	
				(8 in.)	(10 in.)	(8 in.)	(6 in.)
Area	cm ²	-	-	709	1578*	827	621
	(in. ²)	-	-	110	245*	128	96
Temperature		°C	-	20	-195	20	20
H ₂							
Rate	l/s / cm ²	-	-	2.6	17	2.6	2.6
Speed	l/s	-	-	1.843	12.053	2.150	1.614
CO							
Rate	l/s / cm ²	-	-	8.2	11	8.2	8.2
Speed	l/s	-	-	5.814	7.799	6.780	5.092
H ₂ O							
Rate	l/s / cm ²	-	-	7.3	14.6	7.3	7.3
Speed	l/s	-	-	5.176	23.039	6.037	4.533
Mounting flange		in.	2 3/4 CFF (DN 40)	8 CFF (DN 160)	10 CFF (DN 200)	8 CFF (DN 160)	6 CFF (DN 100)
Weight			3.1 - 3.5 grams	8 kg (17.5 lbs)	8 kg (17.5 lbs)	6 kg (13 lbs)	6 kg (13 lbs)
Surface area		mm ² (sq in.)	-	70,900 (110)	70,900 (110)	82,700 (128)	82,700 (128)
Liquid volume		l	-	1.15	1.15	-	-

*Applies to H₂O speed only

Log in on the Gamma website: www.gammavacuum.com for specification sheets, manuals and more information.

Ordering Information

	TSP Filament Cartridges		Liquid Cryoshroud		Ambient Sputter Shield	
			(8 in.)	(10 in.)	(8 in.)	(6 in.)
	Part No.	Part No.	Part No.	Part No.	Part No.	Part No.
TSP Cryoshroud	—	G360051	G360685	—	—	—
TSP Ambient Shield, X2 3/4"	—	—	—	—	G360044	G360190
TSP, 1 FILAMENT, 2.75 CF, MS	G360549	—	—	—	—	—
TSP, 3 FILAMENT, 2.75 CF, MS, STD	G360819	—	—	—	—	—

NEG Non-Evaporable Getter Pumps



Non-evaporable getter (NEG) pumps operate with a non evaporable, compact getter material with a porous structure. The gas molecules either adsorb on the surface of the getter material or diffuse rapidly into it. The NEG pump contains a heating element which is used for regeneration. The getter material consists of a zirconium-aluminum alloy which allows for

hydrocarbon-free operation. After activation the pump operates at room temperature without consumption of electrical energy. A great advantage is the absence of vibrations. Similar to TSPs, NEG pumps are often combined with ion getter pumps. Such combinations are especially useful when a lower pressure is desired. In UHV, hydrogen plays the dominant role and NEG

pumps have a particularly high pumping speed for that. Applications, in which NEG pumps are often used, are particle accelerators, surface analysis instruments, SEM columns and sputtering systems.

Technical Data

		NEG				
		50NP	100NP	200NP	300NP	400NP
Pumping speed *						
H ₂	l/s	55	106	208	312	412
CO (25°C)	l/s	27	51	94	125	156
Sorption capacity *						
H ₂	torr x l	630	1170	2160	2880	3600
CO (25°C)	torr x l	0.1	0.2	0.4	0.6	0.8
CO (total)	torr x l	284	526	972	1296	1620
Alloy composition	%	Zr (70), V (24.6), Fe (5.4)				
Getter mass	g	31.5	58	108	144	180
Getter surface area	cm ²	187	348	642	856	1070
Total mass	kg (lbs)	0.48 (1.05)	0.54 (1.19)	0.75 (1.65)	0.80 (1.79)	0.85 (1.87)
Flange		DN 40 (2.75 in) CFF				

*Pumping speeds reference initial speed values at 25° C exposed configuration

Log in on the Gamma website: www.gammavacuum.com for specification sheets, manuals and more information.

Ordering Information

		NEG				
		50NP	100NP	200NP	300NP	400NP
	Part No.	Part No.	Part No.	Part No.	Part No.	Part No.
NEG Non-Evaporable Getter Pumps	50NP	100NP	200NP	300NP	400NP	

DIGITEL SPC_{NEG} - NEG Pump Controller



Creating ultra-high vacuum is a huge challenge, no matter what the type of application. Analytical instruments, accelerators for medical treatment, fundamental physics research, electron microscopes, and a broad spectrum of various experiments require pressure levels that demand intense preparation. Many components need to be considered in complex systems, so the less worries the better.

GAMMA's new DIGITEL SPC_{NEG} controller serves this purpose. It operates NEG pumps with a high pumping speed for hydrogen, which is the most relevant gas type in ultra-high vacuum. Unlike standard power supplies, the SPC_{NEG} can not only push a current into the NEG's heater, but uses pre-defined routines, with certain

parameters, such as current values or heating duration. Those values are chosen by the SPC_{NEG} depending on the connected NEG pump. The routines are customizable to allow for experiments with different parameters. Reliable operation is accomplished by open-loop detection as well as over-load protection.

High ease-of-use is established by a large touch screen. In addition, the ethernet interface allows for remote control. The new DIGITEL SPC_{NEG} is a milestone in GAMMA's product portfolio: a modern NEG controller in a compact design, optimized in both performance and cost with increased functionality that helps to reach ultra-high vacuum more conveniently for your application.

Advantage for the User

Ease of Use

- Pre-defined routine
- Bright color touch panel
- Intuitive operation

Communications

Ethernet is the standard interface for the SPC_{NEG}. It is used for

- Software updates
- Data logging
- Remote control

Operation

The DIGITEL SPC_{NEG} activates, conditions or regenerates all of GAMMA's NEG pumps as well as any NEG pump on the market with a pumping speed of up to 400 l/s.

Technical Data

DIGITEL SPC_{NEG}

Input power		
Voltage	V	90 – 240
Frequency	Hz	48 – 62
Output power		
Independent outputs		1
Open circuit voltage	VDC	0 – 27
Current (maximum)	A	10
Watts (maximum)	W	270
Resolution	mA	10
Voltage connections		Fischer Type 105
Display		
Type		320 x 240 touchscreen with backlight
Readouts		Power, current, and programmable options
Communications		Ethernet
Conformity to norms		EN 55011 Class A, IEC 801-2, EN 801-3, IEC 801-4, EN 61010-1
Weight	kg	2.0
	lbs	4.5
Size		2U high. 1/4 rack wide, 11.3 in. deep (82 x 110 x 288 mm)
Additional features		AUTOSTART / AUTORUN

Log in on the Gamma website: www.gammavacuum.com for specification sheets, manuals and more information.

Ordering Information

DIGITEL SPC_{NEG}

	Part No.
DIGITEL SPC-NEG	
Ethernet, 110 V US	SPCNSU1E
Ethernet, 220 V US	SPCNSU2E
Ethernet, 230 V EC	SPCNSU2E
Ethernet, 230 V UK	SPCNSK2E
Ethernet, 230 V AU	SPCNSA2E
Cable SPC-NEG	
1 m, small connector (suitable for 50NP - 400NP)	FI4S1MSS
3 m, small connector (suitable for 50NP - 400NP)	FI4S3MSS
6 m, small connector (suitable for 50NP - 400NP)	FI4S6MSS
1 m, large connector (suitable for 410NP)	FI4S1MSL
3 m, large connector (suitable for 410NP)	FI4S3MSL
6 m, large connector (suitable for 410NP)	FI4S6MSL

Sales and Service

Germany

Leybold GmbH

Bonner Strasse 498
D-50968 Cologne
T: +49-(0)221-347 1234
F: +49-(0)221-347 31234
sales@leybold.com
www.leybold.com

Leybold GmbH

Sales Area North
Branch Office Berlin
Industriestrasse 10b
D-12099 Berlin
T: +49-(0)30-435 609 0
F: +49-(0)30-435 609 10
sales.bn@leybold.com

Leybold GmbH

Sales Office South
Branch Office Munich
Karl-Hammerschmidt-Strasse 34
D-85609 Aschheim-Dornach
T: +49-(0)89-357 33 9-10
F: +49-(0)89-357 33 9-33
sales.mn@leybold.com
service.mn@leybold.com

Leybold Dresden GmbH

Service Competence Center
Zur Wetterwarte 50, Haus 304
D-01109 Dresden
Service:
T: +49-(0)351-88 55 00
F: +49-(0)351-88 55 041
info.dr@leybold.com

Europe

Belgium

Leybold Nederland B.V.

Belgisch bijkantoor
Leuvensesteenweg 542
B-1930 Zaventem
Sales:
T: +32-2-711 00 83
F: +32-2-720 83 38
sales.zv@leybold.com
Service:
T: +32-2-711 00 82
F: +32-2-720 83 38
service.zv@leybold.com

France

Leybold France S.A.S.

Parc du Technopolis, Bâtiment Beta
3, Avenue du Canada
F-91940 Les Ulis cedex
Sales and Service:
T: +33-1-69 82 48 00
F: +33-1-69 07 57 38
sales.or@leybold.com
orsay.sav@leybold.com

Leybold France S.A.S.

Valence Factory
640, Rue A. Bergès
B.P. 107
F-26501 Bourg-lès-Valence Cedex
T: +33-4-75 82 33 00
F: +33-4-75 82 92 69
marketing.vc@leybold.com

Great Britain

Leybold UK LTD.

Unit 9
Silverglade Business Park
Leatherhead Road
Chessington
Surrey (London)
KT9 2QL
Sales:
T: +44-13-7273 7300
F: +44-13-7273 7301
sales.ln@leybold.com
Service:
T: +44-13-7273 7320
F: +44-13-7273 7303
service.ln@leybold.com

Italy

Leybold Italia S.r.l.

Via Filippo Brunelleschi 2
I-20093 Cologno Monzese
Sales:
T: +39-02-27 22 31
F: +39-02-27 20 96 41
sales.mi@leybold.com
Service:
T: +39-02-27 22 31
F: +39-02-27 22 32 17
service.mi@leybold.com

Netherlands

Leybold Nederland B.V.

Floridadreef 102
NL-3565 AM Utrecht
Sales and Service:
T: +31-(30) 242 63 30
F: +31-(30) 242 63 31
sales.ut@leybold.com
service.ut@leybold.com

Russia

Leybold Russia

Vashutinskoe Road 15,
Khimki, Moscow region,
141402
Russia
T: +7 495 933 55 50
LeyboldRussia@leybold.com

Switzerland

Leybold Schweiz AG

Hinterbergstrasse 56
CH-6312 Steinhausen
Warehouse and shipping address:
Riedthofstrasse 214
CH-8105 Regensdorf
Sales:
T: +41-44-308 40 50
F: +41-44-308 40 60
sales.zh@leybold.com
Service:
T: +41-44-308 40 62
F: +41-44-308 40 60
service.zh@leybold.com

Spain

Leybold Hispánica, S.A.

C/. Huelva, 7
E-08940 Cornellà de Llobregat
(Barcelona)
Sales:
T: +34-93-666 43 11
F: +34-93-666 43 70
sales.ba@leybold.com
Service:
T: +34-93-666 46 11
F: +34-93-685 43 70
service.ba@leybold.com

Leybold GmbH

Bonner Strasse 498
D-50968 Cologne
T: +49-(0)221-347-0
F: +49-(0)221-347-1250
info@leybold.com

America

USA

Leybold USA Inc.

6005 Enterprise Drive
Export, PA 15632
USA
Sales and Service:
T: +1-800-764-5369
F: +1-800-325-4353
F: +1-800-215-7782
sales.ex@leybold.com
service.ex@leybold.com

Brazil

Leybold do Brasil Ltda.

Av. Tamboré, 937, Tamboré
Distrito Industrial
CEP 06460-000 Barueri - SP
Sales und Service:
T: +55 11 3376 4604
info.ju@leybold.com

Asia

P. R. China

Leybold (Tianjin)

International Trade Co. Ltd.
Beichen Economic
Development Area (BEDA),
No. 8 Western Shuangchen Road
Tianjin 300400
China
Sales and Service:
T: +86-400 038 8989
T: +86-800 818 0033
F: +86-22-2697 4061
F: +86-22-2697 2017
sales.tj@leybold.com
service.tj@leybold.com



India

Leybold India Pvt Ltd.

T-97/2, MIDC Bhosari
Pune-411 026
Indien
Sales and Service:
T: +91-80-2783 9925
F: +91-80-2783 9926
sales.bgl@leybold.com
service.bgl@leybold.com

Japan

Leybold Japan Co., Ltd.

Shin-Yokohama A.K.Bldg., 4th floor
3-23-3, Shin-Yokohama
Kohoku-ku, Yokohama-shi
Kanagawa-ken 222-0033
Japan
Sales:
T: +81-45-471-3330
F: +81-45-471-3323
sales.yh@leybold.com

Malaysia

Leybold Malaysia

Leybold Singapore Pte Ltd.

No. 1 Jalan Hi-Tech 2/6
Kulim Hi-Tech Park
Kulim, Kedah Darul
Aman 09090
Malaysia
Sales and Service:
T: +604 4020 222
F: +604 4020 221
sales.ku@leybold.com
service.ku@leybold.com

South Korea

Leybold Korea Ltd.

25, Hwangsaeul-ro 258 beon-gil,
undang-gu, Seongnam-si,
Gyeonggi-do,
(7F Sunae Finance Tower)
13595 Bundang
Sales:
T: +82-31 785 1367
F: +82-31 785 1359
sales.bd@leybold.com
Service:
T: +82-41 589 3035
F: +82-41 588 0166
service.cn@leybold.com

Singapore

Leybold Singapore Pte Ltd.

42 Loyang Drive
Loyang Industrial Estate
Singapore 508962
Singapore
Sales and Service:
T: +65-6303 7030
F: +65-6773 0039
info.sg@leybold.com

Taiwan

Leybold Taiwan Ltd.

10F., No. 32, Chenggong 12th St.,
Zhubei City, Hsinchu County 302
Taiwan, R.O.C.
Sales and Service:
T: +886-3-500 1688
F: +886-3-550 6523
info.hc@leybold.com



www.leybold.com